

IN THE CLAIMS

Please amend the claims as follows:

1. (currently amended) A radio frequency (RF) receiver comprising:

a local oscillator (LO) for generating a local oscillation signal;

first and a second mixers coupled to said LO, for converting a received RF signal to an in-phase intermediate frequency (IF) signal and a quadrature IF signal, respectively;

an LO frequency control module, coupled to said LO, for alternately down-converting a channel frequency on a frame-by-frame basis by changing an oscillation frequency of said LO via

even frame: $f_{\text{RFLO}} = f_{\text{CH}} - f_{\text{IF}}$

odd frame: $f_{\text{RFLO}} = f_{\text{CH}} + f_{\text{IF}}$

wherein f_{RFLO} = said local oscillation frequency

f_{CH} = said channel frequency

f_{IF} = said IF signal frequency;

a down converter, coupled to said first and second mixers, for down converting said in-phase IF signal and said quadrature IF signal to a baseband;

a complex sinusoid signal IFLO, coupled to said down converter, for providing a complex sinusoid signal to said down converter; and

a down conversion controller, coupled to said complex sinusoid signal IFLO, for adjusting a complex sine wave within said down converter via said complex sinusoid signal IFLO.

Please cancel Claims 2-3.

4. (currently amended) The RF receiver of Claim 3 1, wherein said down conversion controller adjusts a complex sine wave $e^{\pm j\omega t}$ within said down converter by

$$\begin{aligned} \text{even frame: } IFLO(t) &= e^{-j\omega_{IF}t} \\ \text{odd frame: } IFLO(t) &= e^{+j\omega_{IF}t} \end{aligned}$$

$$\begin{aligned} \text{wherein } e^{-j\omega_{IF}t} &= \cos\omega_{IF}t - j\sin\omega_{IF}t \\ e^{+j\omega_{IF}t} &= \cos\omega_{IF}t + j\sin\omega_{IF}t \\ \omega_{IF} &= 2\pi f_{IF} \end{aligned}$$

5. (original) The RF receiver of Claim 4, wherein said frames are time-division multiple access (TDMA) frames.

6. (currently amended) The RF receiver of Claim 3 1, wherein said down conversion controller adjusts a complex sine wave $e^{\pm j\omega t}$ within said down converter by

$$\begin{aligned} \text{even frame: } IFLO(t) &= e^{+j\omega_{IF}t} \\ \text{odd frame: } IFLO(t) &= e^{-j\omega_{IF}t} \end{aligned}$$

$$\begin{aligned} \text{where } e^{-j\omega_{IF}t} &= \cos\omega_{IF}t - j\sin\omega_{IF}t \\ e^{+j\omega_{IF}t} &= \cos\omega_{IF}t + j\sin\omega_{IF}t \\ \omega_{IF} &= 2\pi f_{IF} \end{aligned}$$

7. (original) The RF receiver of Claim 6, wherein said frames are time-division multiple access (TDMA) frames.

8. (currently amended) The RF receiver of Claim 2 1, wherein said LO frequency control module alternately down-converts a channel frequency by

even frame: $f_{\text{RFLO}} = f_{\text{CH}} + f_{\text{IF}}$
 odd frame: $f_{\text{RFLO}} = f_{\text{CH}} - f_{\text{IF}}$
wherein f_{RFLO} = said local oscillation frequency
 f_{CH} = said channel frequency
 f_{IF} = said IF signal frequency

9. (original) The RF receiver of Claim 8, wherein said down conversion controller adjusts a complex sine wave $e^{\pm j\omega t}$ within said down converter by

$$\begin{aligned} \text{even frame: } IFLO(t) &= e^{+j\omega_{IF}t} \\ \text{odd frame: } IFLO(t) &= e^{-j\omega_{IF}t} \end{aligned}$$

$$\begin{aligned} \text{wherein } e^{-j\omega_{IF}t} &= \cos\omega_{IF}t - j\sin\omega_{IF}t \\ e^{+j\omega_{IF}t} &= \cos\omega_{IF}t + j\sin\omega_{IF}t \\ \omega_{IF} &= 2\pi f_{IF} \end{aligned}$$

10. (original) The RF receiver of Claim 9, wherein said frames are time-division multiple access (TDMA) frames.

11. (original) The RF receiver of Claim 8, wherein said down conversion controller adjusts a complex sine wave $e^{\pm j\omega t}$ within said down converter by

$$\begin{aligned} \text{even frame: } IFLO(t) &= e^{-j\omega_{IF}t} \\ \text{odd frame: } IFLO(t) &= e^{+j\omega_{IF}t} \end{aligned}$$

$$\begin{aligned} \text{wherein } e^{-j\omega_{IF}t} &= \cos\omega_{IF}t - j\sin\omega_{IF}t \\ e^{+j\omega_{IF}t} &= \cos\omega_{IF}t + j\sin\omega_{IF}t \\ \omega_{IF} &= 2\pi f_{IF} \end{aligned}$$

12. (original) The RF receiver of Claim 11, wherein said frames are time-division multiple access (TDMA) frames.

13. (original) The RF receiver of Claim 1, wherein said RF receiver further includes an IF filter.

14. (original) The RF receiver of Claim 1, wherein said RF receiver further includes an analog-to-digital converter.

15. (currently amended) A method for enhancing signal quality within a radio frequency (RF) receiver, said method comprising:

receiving a RF signal;

alternately down-converting a channel frequency by changing a local oscillation frequency, wherein said local oscillation frequency is utilized for converting said received RF signal to an in-phase intermediate frequency (IF) signal and a quadrature IF signal, wherein said alternately down-converting further includes alternately down-converting said in-phase IF signal and said quadrature IF signal on a frame-by-frame basis by

even frame: $f_{\text{RFLO}} = f_{\text{CH}} - f_{\text{IF}}$

odd frame: $f_{\text{RFLO}} = f_{\text{CH}} + f_{\text{IF}}$

wherein f_{RFLO} = said local oscillation frequency

f_{CH} = said channel frequency

f_{IF} = said IF signal frequency;

providing a complex sine wave for down converting said in-phase IF signal and said quadrature IF signal; and

adjusting said complex sine wave when down converting said in-phase IF signal and said quadrature IF signal to a baseband signal.

Please cancel Claims 16-17.

18. (currently amended) The method of Claim ~~17~~ 15, wherein said adjusting further includes adjusting a complex sine wave $e^{\pm j\omega t}$ by

$$\text{even frame: } IFLO(t) = e^{-j\omega_{IF}t}$$

$$\text{odd frame: } IFLO(t) = e^{+j\omega_{IF}t}$$

$$\text{wherein } e^{-j\omega_{IF}t} = \cos\omega_{IF}t - j\sin\omega_{IF}t$$

$$e^{+j\omega_{IF}t} = \cos\omega_{IF}t + j\sin\omega_{IF}t$$

$$\omega_{IF} = 2\pi f_{IF}$$

19. (original) The method of Claim 18, wherein said frames are time-division multiple access (TDMA) frames.

20. (currently amended) The method of Claim ~~17~~ 15, wherein said adjusting further includes adjusting a complex sine wave $e^{\pm j\omega t}$ by

$$\text{even frame: } IFLO(t) = e^{+j\omega_{IF}t}$$

$$\text{odd frame: } IFLO(t) = e^{-j\omega_{IF}t}$$

$$\text{wherein } e^{-j\omega_{IF}t} = \cos\omega_{IF}t - j\sin\omega_{IF}t$$

$$e^{+j\omega_{IF}t} = \cos\omega_{IF}t + j\sin\omega_{IF}t$$

$$\omega_{IF} = 2\pi f_{IF}$$

21. (original) The method of Claim 20, wherein said frames are time-division multiple access (TDMA) frames.

22. (currently amended) The method of Claim 47 15, wherein said alternately down-converting is performed by

$$\text{even frame:} \quad f_{\text{RFLO}} = f_{\text{CH}} + f_{\text{IF}}$$

$$\text{odd frame:} \quad f_{\text{RFLO}} = f_{\text{CH}} - f_{\text{IF}}$$

wherein f_{RFLO} = said local oscillation frequency
 f_{CH} = said channel frequency
 f_{IF} = said IF signal frequency

23. (original) The method of Claim 22, wherein said adjusting further includes adjusting a complex sine wave $e^{\pm j\omega t}$ by

$$\text{even frame: } IFLO(t) = e^{+j\omega_{\text{IF}}t}$$

$$\text{odd frame: } IFLO(t) = e^{-j\omega_{\text{IF}}t}$$

$$\text{wherein } e^{-j\omega_{\text{IF}}t} = \text{Cos}\omega_{\text{IF}}t - j\text{Sin}\omega_{\text{IF}}t$$

$$e^{+j\omega_{\text{IF}}t} = \text{Cos}\omega_{\text{IF}}t + j\text{Sin}\omega_{\text{IF}}t$$

$$\omega_{\text{IF}} = 2\pi f_{\text{IF}}$$

24. (original) The method of Claim 23, wherein said frames are time-division multiple access (TDMA) frames.

25. (original) The method of Claim 22, wherein said adjusting further includes adjusting a complex sine wave $e^{tj\omega t}$ by

$$\begin{aligned} \text{even frame: } IFLO(t) &= e^{-j\omega_{IF}t} \\ \text{odd frame: } IFLO(t) &= e^{+j\omega_{IF}t} \end{aligned}$$

$$\begin{aligned} \text{wherein } e^{-j\omega_{IF}t} &= \cos\omega_{IF}t - j\sin\omega_{IF}t \\ e^{+j\omega_{IF}t} &= \cos\omega_{IF}t + j\sin\omega_{IF}t \\ \omega_{IF} &= 2\pi f_{IF} \end{aligned}$$

26. (original) The method of Claim 25, wherein said frames are time-division multiple access (TDMA) frames.

27-40. cancelled